

View Online at <https://aerobasegroup.com/nsn/5340-01-561-4714>

**First Leg Length:**

5.000 inches

**Second Leg Length:**

10.000 inches

**End Application:**

2320-01-528-6294 truck, tank

**Second Leg Width:**

4.940 inches

**Second Leg Corner Radius:**

0.250 inches

**First Leg Hole Diameter:**

0.406 inches

**Second Leg Hole Diameter:**

0.281 inches

**Second Leg Distance Between Hole Centers Along Width:**

3.188 inches

**Second Leg Distance Between Hole Centers Along Length:**

2.250 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.875 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.875 inches

**First Leg Thickness:**

0.188 inches

**Second Leg Thickness:**

0.188 inches

**First Leg Width:**

4.940 inches

**First Leg Corner Radius:**

0.250 inches

**First Leg Distance Between Hole Centers Along Width:**

3.188 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.875 inches

**First Leg Distance From Edge To Hole Center Along Length:**

1.250 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

Four holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Product Name:**

Bracket, mounting, windshield deluge

**Material:**

Steel

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0