

View Online at <https://aerobasegroup.com/nsn/5340-01-567-6704>

First Leg Length:

Between 43.0 millimeters and 47.0 millimeters

Second Leg Length:

Between 77.0 millimeters and 81.0 millimeters

End Application:

2320-01-549-8565; truck, cargo

Second Leg Width:

Between 48.0 millimeters and 52.0 millimeters

Second Leg Corner Radius:

12.0 millimeters

First Leg Slot Length:

15.0 millimeters

First Leg Slot Width:

Between 5.0 millimeters and 15.0 millimeters

Second Leg Hole Diameter:

Between 5.0 millimeters and 15.0 millimeters

Second Leg Distance Between Hole Centers Along Length:

35.0 major inches

Second Leg Distance From Edge To Hole Center Along Width:

25.0 millimeters

Second Leg Distance From Edge To Hole Center Along Length:

28.0 millimeters

First Leg Thickness:

0.134 inches

Second Leg Thickness:

0.134 inches

First Leg Width:

Between 48.0 millimeters and 52.0 millimeters

First Leg Corner Radius:

12.0 millimeters

First Leg Distance From Edge To Hole Center Along Width:

25.0 millimeters

First Leg Distance From Edge To Hole Center Along Length:

20.0 millimeters

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

One slot

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Err Default:

Err default

Product Name:

Angle, brace

Material:

Steel

Material Specification:

Astm a1008/a1008m, sheet. Cold rolled assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0