

View Online at <https://aerobasegroup.com/nsn/5340-01-568-1084>

First Leg Length:

55.0 millimeters

Second Leg Length:

Between 98.0 millimeters and 102.0 millimeters

End Application:

2320-01-447-3892 truck, wrecker

Second Leg Width:

Between 59.5 millimeters and 62.5 millimeters

Second Leg Corner Radius:

Between 1.0 millimeters and 5.0 millimeters

First Leg Hole Diameter:

Between 10.5 millimeters and 11.1 millimeters

Second Leg Hole Diameter:

Between 10.5 millimeters and 11.1 millimeters

Second Leg Distance Between Hole Centers Along Length:

49.7 major mils and 50.7 major centimeters

First Leg Width:

Between 125.0 millimeters and 129.0 millimeters

First Leg Corner Radius:

Between 1.0 millimeters and 5.0 millimeters

First Leg Distance Between Hole Centers Along Width:

Between 49.8 millimeters and 50.8 millimeters

First Leg Distance From Edge To Hole Center Along Width:

42.0 millimeters

First Leg Distance From Edge To Hole Center Along Length:

19.0 millimeters

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

Between 5.0 degrees and 11.0 degrees

Second Leg Angle:

Between 5.0 degrees and 11.0 degrees

Product Name:

Bracket, guide

Material:

Steel

Material Specification:

Astm a36 assn standard single material response

Surface Treatment:

Paint

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0