

View Online at <https://aerobasegroup.com/nsn/5340-01-568-3303>

**First Leg Length:**

150.0 millimeters

**Second Leg Length:**

150.0 millimeters

**End Application:**

2320-01-549-8565, truck, cargo

**Second Leg Width:**

30.0 millimeters

**First Leg Hole Diameter:**

10.0 millimeters

**Second Leg Hole Diameter:**

7.5 millimeters

**Second Leg Distance Between Hole Centers Along Length:**

80.0 major inches

**Second Leg Distance From Edge To Hole Center Along Width:**

10.0 millimeters

**Second Leg Distance From Edge To Hole Center Along Length:**

35.0 millimeters

**First Leg Thickness:**

0.075 inches

**Second Leg Thickness:**

0.075 inches

**First Leg Width:**

20.0 millimeters

**First Leg Distance Between Hole Centers Along Length:**

100.0 millimeters

**First Leg Distance From Edge To Hole Center Along Width:**

12.9 millimeters

**First Leg Distance From Edge To Hole Center Along Length:**

25.0 millimeters

**First Leg Side Radius:**

10.0 millimeters

**First Leg Style:**

Side radius

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Two holes

**Hole Quantity:**

4

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

1.9 radians

**Product Name:**

Bracket, overhead panel

**Material:**

Steel comp 1008 or steel comp 1011

**Material Specification:**

Astm a1008/a1008m, sheet, cold rolled. 0.047 in thk (14 ga) assn standard single material response or astm a1011/a1011m, sheet, hot rolled. 0.047 in thk (14 ga) assn standard single material response

**Surface Treatment:**

Paint

**Surface Treatment Specification:**

1920-71-242-0325

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0