

View Online at <https://aerobasegroup.com/nsn/5340-01-568-3303>

First Leg Length:

150.0 millimeters

Second Leg Length:

150.0 millimeters

End Application:

2320-01-549-8565, truck, cargo

Second Leg Width:

30.0 millimeters

First Leg Hole Diameter:

10.0 millimeters

Second Leg Hole Diameter:

7.5 millimeters

Second Leg Distance Between Hole Centers Along Length:

80.0 major inches

Second Leg Distance From Edge To Hole Center Along Width:

10.0 millimeters

Second Leg Distance From Edge To Hole Center Along Length:

35.0 millimeters

First Leg Thickness:

0.075 inches

Second Leg Thickness:

0.075 inches

First Leg Width:

20.0 millimeters

First Leg Distance Between Hole Centers Along Length:

100.0 millimeters

First Leg Distance From Edge To Hole Center Along Width:

12.9 millimeters

First Leg Distance From Edge To Hole Center Along Length:

25.0 millimeters

First Leg Side Radius:

10.0 millimeters

First Leg Style:

Side radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Hole Quantity:

4

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

1.9 radians

Product Name:

Bracket, overhead panel

Material:

Steel comp 1008 or steel comp 1011

Material Specification:

Astm a1008/a1008m, sheet, cold rolled. 0.047 in thk (14 ga) assn standard single material response or astm a1011/a1011m, sheet, hot rolled. 0.047 in thk (14 ga) assn standard single material response

Surface Treatment:

Paint

Surface Treatment Specification:

1920-71-242-0325

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0