

View Online at <https://aerobasegroup.com/nsn/5340-01-572-3412>

First Leg Length:

2.500 inches

Second Leg Length:

2.500 inches

End Application:

2320-01-206-4077, truck tractor/5-ton m939 series

Second Leg Width:

30.000 inches

First Leg Hole Diameter:

0.220 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

14.000 inches

Second Leg Distance Between Second And Third Hole Centers Along Width:

8.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.000 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.560 inches

First Leg Thickness:

0.188 inches

Second Leg Thickness:

0.188 inches

First Leg Width:

30.000 inches

First Leg Distance Between First And Second Hole Centers Along Width:

2.880 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

19.480 inches

First Leg Distance From Edge To Hole Center Along Width:

1.380 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Four holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Product Name:

Angle, mud flap stowage, assembly

Special Features:

Nha-2300848, use 2 fasteners 10939516-2 with this

Material:

Steel

Material Specification:

Astm a575, -1020. Hr merchant quality assn standard single material response or astm a376, 1010-1020. Hr special quality assn standard single material response

Surface Treatment:

Primer and paint

Surface Treatment Specification:

Tt-c-490. Ty i or ii federal specification 1st treatment response and mil-p-52192 military specification 2nd treatment response or mil-p-53022 military specification 2nd treatment response or mil-p-53030 military specification 2nd treatment response and mil-c-46168. Green 383/paint thk iaw mil-std-193 military specification 3rd treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-p-52192 spec.