NSN 5340-01-573-1508

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-573-1508

First Leg Length:

Between 38.0 millimeters and 42.0 millimeters

Second Leg Length:

Between 38.0 millimeters and 42.0 millimeters

End Application:

2320-01-353-9098 chassis, truck

First Leg Hole Diameter:

Between 11.4 millimeters and 12.0 millimeters

First Leg Thickness:

4.8 millimeters

Second Leg Thickness:

4.8 millimeters

Center Section Height:

Between 159.0 millimeters and 161.0 millimeters

Center Section Width:

Between 56.5 millimeters and 60.5 millimeters

Center Section Thickness:

4.8 millimeters

First Leg Width:

Between 56.5 millimeters and 60.5 millimeters

First Leg Distance Between Hole Centers Along Width:

Between 27.8 millimeters and 29.2 millimeters

First Leg Distance From Edge To Hole Center Along Width:

Between 14.0 millimeters and 16.0 millimeters

First Leg Distance From Edge To Hole Center Along Length:

Between 13.5 millimeters and 16.5 millimeters

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Identical

First Leg Angle:

Between 4.5 degrees and 7.5 degrees

Second Leg Angle:

Between 4.5 degrees and 7.5 degrees

Product Name:

Bracket, work light

Special Features:

Center section has 1 slot 19.0-21.0 min-max length x 11.7-12.3 min-max width

Material:

Steel

NSN 5340-01-573-1508

Double Angle Bracket - Page 2 of 2



Material Specification:

Astm a366/a366m assn standard single material response

Style Designator:

Adjacent angles

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0