

View Online at <https://aerobasegroup.com/nsn/5340-01-578-1092>

**First Leg Length:**

Between 58.5 millimeters and 61.5 millimeters

**Second Leg Length:**

Between 98.5 millimeters and 101.5 millimeters

**End Application:**

2320-01-508-8859 truck, materials handling-container hoist

**Second Leg Width:**

Between 49.0 millimeters and 51.0 millimeters

**Second Leg Corner Radius:**

Between 8.0 millimeters and 12.0 millimeters

**Second Leg Hole Diameter:**

Between 3.0 millimeters and 3.2 millimeters

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 24.0 millimeters and 26.0 millimeters

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 8.0 millimeters and 8.9 millimeters

**First Leg Thickness:**

3.0 millimeters

**Second Leg Thickness:**

3.0 millimeters

**First Leg Width:**

Between 49.0 millimeters and 51.0 millimeters

**First Leg Corner Radius:**

Between 8.0 millimeters and 12.0 millimeters

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

No hole

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

Between 4.0 degrees and 8.0 degrees

**Product Name:**

Bracket, portable worklight

**Special Features:**

Two round holes, end one hole 17.4-18.0 min-max millimeters dia. And end two hole 26.5-27.5 min-max millimeters dia.

**Material:**

Steel comp 1008 or steel comp 1011

**Material Specification:**

Astm a1008/a1008m assn standard single material response or astm a1011/a1011m assn standard single material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A042a0