

View Online at <https://aerobasegroup.com/nsn/5340-01-579-7318>

First Leg Length:

Between 0.606 inches and 0.616 inches

Second Leg Length:

Between 1.106 inches and 1.116 inches

End Application:

3mh60sc airframe; hydraulic winch assembly; hydraulic hose assembly

Second Leg Width:

0.500 inches

First Leg Slot Length:

Between 0.278 inches and 0.288 inches

First Leg Slot Width:

Between 0.200 inches and 0.210 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.250 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.283 inches

Second Leg Slot Length:

Between 0.268 inches and 0.278 inches

Second Leg Slot Width:

Between 0.200 inches and 0.210 inches

First Leg Thickness:

Between 0.056 inches and 0.068 inches

Second Leg Thickness:

Between 0.056 inches and 0.068 inches

First Leg Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Width:

0.250 inches

First Leg Distance From Edge To Hole Center Along Length:

0.273 inches

First Leg End Radius:

0.500 inches

Second Leg End Radius:

0.500 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One slot

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One slot

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Err Default:

Err default

Second Leg Slot Offset Angle:

0.0 degrees

Product Name:

Inavy: bracket; std: bracket - 90 deg, ams 6350, .190 bolt

Material:

Steel

Material Specification:

Ams 6350, harden (oil quench) and temper to rockwell c32-38 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0