

View Online at <https://aerobasegroup.com/nsn/5340-01-583-6566>

**Width:**

3.380 inches

**Thickness:**

0.187 inches

**Length:**

9.000 inches

**Mounting Hole Diameter:**

0.500 inches third hole

**Mounting Hole Quantity:**

4

**Mounting Hole Type:**

Unthreaded

**Corner Radius:**

0.630 inches

**End Application:**

2320-01-494-7606 and 2355-01-539-3639, both of which are light armored vehicles

**Mounting Configuration:**

One plain unthreaded hole, two holes in a slot shape unthreaded and two holes countersunk unthreaded

**Product Name:**

Mounting plate, rear

**Special Features:**

Center hole distance for two countersunk holes is 4.000 in nom; center hole distance between first unthreaded hole to first slot hole is 4.331 in nom; center distance between first unthreaded hole and second second slot hole is 7.283 in nom; two slotted, unthreaded holes are 2x 0.348 boundry; stamp or engrave cage and part number at location shown on drawing in size 0.125 in characters; finish is 7.2.2 of mil-std-171; thickness is 0.1875 alum plate; nha 12540951; unit weight 0.5 lb

**Material:**

Aluminum alloy 6061

**Material Specification:**

Grade 6061-t2, astm b209 national specification single material response

**Shape:**

Irregular

**Surface Treatment Specification:**

Mil-std-171, color black military standard single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530d0

**Mil-std (military Standard):**

Mil-std-171 spec.