

View Online at <https://aerobasegroup.com/nsn/5340-01-583-6566>

Width:

3.380 inches

Thickness:

0.187 inches

Length:

9.000 inches

Mounting Hole Diameter:

0.500 inches third hole

Mounting Hole Quantity:

4

Mounting Hole Type:

Unthreaded

Corner Radius:

0.630 inches

End Application:

2320-01-494-7606 and 2355-01-539-3639, both of which are light armored vehicles

Mounting Configuration:

One plain unthreaded hole, two holes in a slot shape unthreaded and two holes countersunk unthreaded

Product Name:

Mounting plate, rear

Special Features:

Center hole distance for two countersunk holes is 4.000 in nom; center hole distance between first unthreaded hole to first slot hole is 4.331 in nom; center distance between first unthreaded hole and second second slot hole is 7.283 in nom; two slotted, unthreaded holes are 2x 0.348 boundry; stamp or engrave cage and part number at location shown on drawing in size 0.125 in characters; finish is 7.2.2 of mil-std-171; thickness is 0.1875 alum plate; nha 12540951; unit weight 0.5 lb

Material:

Aluminum alloy 6061

Material Specification:

Grade 6061-t2, astm b209 national specification single material response

Shape:

Irregular

Surface Treatment Specification:

Mil-std-171, color black military standard single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530d0

Mil-std (military Standard):

Mil-std-171 spec.