

View Online at <https://aerobasegroup.com/nsn/5340-01-588-0223>

Mounting Hole Type:

Threaded

First Leg Length:

3.750 inches

Second Leg Length:

4.630 inches

End Application:

2350-01-506-0132 armored reconnaissance-airborne assault

Second Leg Width:

10.250 inches

First Leg Slot Length:

1.690 inches

First Leg Slot Width:

Between 0.405 inches and 0.465 inches

Second Leg Hole Diameter:

0.250 inches

Second Leg Distance Between Hole Centers Along Width:

1.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

2.050 inches

Second Leg Distance From Edge To Hole Center Along Length:

2.940 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

Center Section Height:

5.810 inches

Center Section Width:

10.250 inches

Center Section Thickness:

0.250 inches

First Leg Width:

0.500 inches

First Leg Corner Radius:

10.250 inches

First Leg Distance Between First And Second Hole Centers Along Width:

4.375 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

4.375 inches

First Leg Distance From Edge To Hole Center Along Width:

0.750 inches

First Leg Distance From Edge To Hole Center Along Length:

1.125 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

3 slots

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

0.4 degrees

Second Leg Angle:

0.4 degrees

Product Name:

Z bracket, right

Special Features:

Mounting hole thread unc 2b 0.250-20

Material:

Steel

Material Specification:

Astm a 36 assn standard single material response or astm a 588 assn standard single material response

Surface Treatment:

Paint

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A042a0