
# NSN 5340-01-588-1881

Double Angle Bracket - Page 1 of 2

Mounting Hole Type:





Plain First Leg Length: 70.6 millimeters Second Leg Length: 96.8 millimeters **End Application:** 2320-01-552-7782 truck, dump Second Leg Width: 76.2 millimeters First Leg Hole Diameter: 2.5 millimeters Second Leg Distance Between Hole Centers Along Length: Between 49.8 millimeters and 51.8 millimeters Second Leg Distance From Edge To Hole Center Along Width: Between 44.2 millimeters and 46.2 millimeters Second Leg Distance From Edge To Hole Center Along Length: Between 22.4 millimeters and 28.4 millimeters Second Leg Slot Length: 25.4 millimeters Second Leg Slot Width: Between 10.2 millimeters and 12.2 millimeters **First Leg Thickness:** 4.8 millimeters Second Leg Thickness: 4.8 millimeters **Center Section Height:** 88.9 millimeters **Center Section Width:** 76.2 millimeters **Center Section Thickness:** 4.8 millimeters First Leg Width: 76.2 millimeters First Leg Distance Between Hole Centers Along Width: 60.0 millimeters First Leg Distance Between Hole Centers Along Length: 35.0 millimeters First Leg Distance From Edge To Hole Center Along Width: 8.1 millimeters First Leg Distance From Edge To Hole Center Along Length: 11.2 millimeters

## NSN 5340-01-588-1881

Double Angle Bracket - Page 2 of 2



First Leg Style:

Square

First Leg Hole Arrangement Style:

Four holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

6.0 degrees

Second Leg Angle:

6.0 degrees

#### **Product Name:**

Bracket, hanger, tail pipe

#### **Special Features:**

Center leg has one hole 10.7-11.7 min-max millimeters in dia

Material:

Steel

#### Material Specification:

Astm a36/a36m assn standard single material response or astm a1008/a1008m assn standard single material response

### Style Designator:

Double angle

#### Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A042a0