## NSN 5340-01-591-3243

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-591-3243

**Mounting Hole Type:** 

Plain

First Leg Length:

Between 5.6 millimeters and 7.2 millimeters

Second Leg Length:

Between 37.1 millimeters and 39.1 millimeters

**End Application:** 

Howitzer, 155mm, m777e1

Second Leg Width:

37.1 major mils and 39.1 major centimeters

Second Leg Hole Diameter:

8.8 major mils and 9.2 major centimeters

Second Leg Distance From Edge To Hole Center Along Width:

19.1 major inches

Second Leg Distance From Edge To Hole Center Along Length:

19.1 millimeters

First Leg Thickness:

Between 2.9 millimeters and 3.5 millimeters

Second Leg Thickness:

Between 2.9 millimeters and 3.5 millimeters

First Leg Width:

Between 37.1 millimeters and 39.1 millimeters

Second Leg Side Radius:

Between 2.8 millimeters and 3.4 millimeters

First Leg Style:

Square

First Leg Hole Arrangement Style:

No hole

Second Leg Style:

Side radius

**Second Leg Hole Arrangement Style:** 

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

Between 2.8 degrees and 3.4 degrees

**Product Name:** 

Clamp, plate, mount

Material:

Steel

**Material Specification:** 

Astm a36/a36m assn standard single material response

## NSN 5340-01-591-3243

Angle Bracket - Page 2 of 2

Mil-std (military Standard):

Mil-dtl-16232 spec.



Surface Treatment:
Phosphate
Surface Treatment Specification:
Mil-dtl-16232, type m or z, class 3, color green 34094 military standard single treatment response
Style Designator:
Angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A042a0