

View Online at <https://aerobasegroup.com/nsn/5340-01-591-3256>

Mounting Hole Type:

Plain

First Leg Length:

Between 56.2 millimeters and 58.2 millimeters

Second Leg Length:

Between 87.9 millimeters and 89.9 millimeters

End Application:

Howitzer, 155mm, m777e1

Second Leg Width:

75.2 major mils and 77.2 major centimeters

Second Leg Corner Radius:

Between 11.7 millimeters and 13.7 millimeters

First Leg Hole Diameter:

6.8 major mils and 7.2 major centimeters

Second Leg Distance From Edge To Hole Center Along Width:

38.1 major inches

Second Leg Distance From Edge To Hole Center Along Length:

57.1 millimeters

Second Leg Slot Length:

Between 32.0 millimeters and 32.2 millimeters

Second Leg Slot Width:

Between 30.4 millimeters and 30.7 millimeters

First Leg Thickness:

Between 2.9 millimeters and 3.5 millimeters

Second Leg Thickness:

Between 2.9 millimeters and 3.5 millimeters

First Leg Width:

Between 170.5 millimeters and 172.5 millimeters

First Leg Corner Radius:

Between 5.4 millimeters and 7.4 millimeters

First Leg Distance Between Hole Centers Along Width:

109.2 millimeters

First Leg Distance From Edge To Hole Center Along Width:

31.1 millimeters

First Leg Distance From Edge To Hole Center Along Length:

38.1 millimeters

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

One slot

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

Between 5.4 degrees and 7.4 degrees

Product Name:

Bracket, connector w2j1

Material:

Stainless steel

Material Specification:

Astm a693, stainless steel type 630 assn standard single material response or ams 5528, stainless steel, type 17-7 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A042a0