

View Online at <https://aerobasegroup.com/nsn/5340-01-591-3274>

First Leg Length:

Between 75.2 millimeters and 77.2 millimeters

Second Leg Length:

Between 100.6 millimeters and 102.6 millimeters

End Application:

Howitzer, 155mm, m777e1

Second Leg Width:

62.5 major mils and 64.5 major centimeters

Second Leg Corner Radius:

Between 5.4 millimeters and 7.4 millimeters

First Leg Hole Diameter:

8.2 major mils and 8.8 major centimeters

Second Leg Hole Diameter:

7.6 major mils and 7.7 major centimeters

Second Leg Distance Between Hole Centers Along Width:

44.5 millimeters

Second Leg Distance Between Hole Centers Along Length:

44.5 major inches

Second Leg Distance From Edge To Hole Center Along Width:

31.8 major inches

Second Leg Distance From Edge To Hole Center Along Length:

69.9 millimeters

First Leg Thickness:

Between 4.6 millimeters and 4.9 millimeters

Second Leg Thickness:

Between 4.6 millimeters and 4.9 millimeters

First Leg Width:

Between 62.5 millimeters and 64.5 millimeters

First Leg Corner Radius:

Between 5.4 millimeters and 7.4 millimeters

First Leg Distance Between Hole Centers Along Width:

38.0 millimeters

First Leg Distance Between Hole Centers Along Length:

38.0 millimeters

First Leg Distance From Edge To Hole Center Along Width:

12.7 millimeters

First Leg Distance From Edge To Hole Center Along Length:

25.4 millimeters

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Four holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

Between 5.4 degrees and 7.4 degrees

Product Name:

Bracket, mounting

Material:

Stainless steel

Material Specification:

Astm a693, stainless steel type 630 assn standard single material response or asm 5528, stainless steel type 17-7 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A042a0