

View Online at <https://aerobasegroup.com/nsn/5340-01-594-5591>

First Leg Length:

Between 1.208 inches and 1.228 inches

Second Leg Length:

Between 1.240 inches and 1.260 inches

End Application:

INDE-XD-RIV-E,10

Second Leg Width:

Between 1.240 inches and 1.260 inches

Second Leg End Width:

Between 0.802 inches and 0.822 inches

First Leg Hole Diameter:

Between 0.216 inches and 0.223 inches

Second Leg Hole Diameter:

Between 0.653 inches and 0.666 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.896 inches and 0.916 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.740 inches and 0.760 inches

First Leg Thickness:

Between 0.177 inches and 0.197 inches

Second Leg Thickness:

Between 0.177 inches and 0.197 inches

First Leg Width:

Between 1.802 inches and 1.822 inches

First Leg Distance Between Hole Centers Along Width:

Between 1.428 inches and 1.448 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.178 inches and 0.198 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.269 inches and 0.289 inches

Second Leg End Radius:

0.250 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius and tapered

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

0.250 radians

Second Leg Chamfer Angle:

Between 57.0 degrees and 63.0 degrees

Product Name:

Bracket, switch

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-225/8 t6 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Nuk-a-8625 type 2, class 2 (black) military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

spec.