

View Online at <https://aerobasegroup.com/nsn/5340-01-595-9436>

Mounting Hole Type:

Plain

First Leg Length:

Between 0.745 inches and 0.775 inches

Second Leg Length:

Between 0.935 inches and 0.965 inches

Second Leg Width:

Between 0.615 inches and 0.635 inches

Second Leg Corner Radius:

Between 0.490 inches and 0.510 inches

First Leg Hole Diameter:

Between 0.322 inches and 0.332 inches

Second Leg Hole Diameter:

Between 0.200 inches and 0.210 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.307 inches and 0.317 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.195 inches and 0.205 inches

First Leg Thickness:

Between 0.056 inches and 0.068 inches

Second Leg Thickness:

Between 0.056 inches and 0.068 inches

First Leg Width:

Between 0.615 inches and 0.635 inches

First Leg Corner Radius:

Between 0.490 inches and 0.510 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.307 inches and 0.317 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.255 inches and 0.265 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

Between 85.0 degrees and 95.0 degrees

Product Name:

Bracket, angle, 90degrees, cres uns s41000, .190 x .312 bolt

Material:

Steel

Material Specification:

Ams5504 assn standard all material responses

Surface Treatment:

Passivate

Surface Treatment Specification:

Ams2250 assn standard all treatment responses

Style Designator:

Angle

Specification Data:

81343-as9602 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0