

View Online at <https://aerobasegroup.com/nsn/5340-01-605-1878>

Mounting Hole Type:

Plain

First Leg Length:

1.560 inches

Second Leg Length:

1.650 inches

End Application:

Integrated family of test equipment (ifte)

Second Leg Width:

2.500 inches

First Leg Hole Diameter:

0.875 inches

Second Leg Hole Diameter:

0.375 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.250 millimeters

Second Leg Distance From Edge To Hole Center Along Length:

0.860 inches

First Leg Thickness:

0.190 inches

Second Leg Thickness:

0.190 inches

First Leg Width:

2.500 inches

First Leg Distance From Edge To Hole Center Along Width:

1.250 inches

First Leg Distance From Edge To Hole Center Along Length:

0.810 inches

First Leg End Radius:

0.750 inches

Second Leg End Radius:

0.750 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

0.20 degrees

First Leg Offset Angle:

30.0 degrees

Product Name:

Bracket, anchor, tie down

Material:

Steel comp 304

Material Specification:

Astm a666, condition a, number 2b assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-f-14072 military specification single treatment response

Style Designator:

Offset angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-f-14072 spec.