NSN 5340-01-605-2604

Swivel Caster - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-605-2604

| Center To Center Distance Between Bolt Holes Along Width: |
|--|
| 2.62 inches |
| Center To Center Distance Between Bolt Holes Along Length: |
| 3.63 inches |
| End Application: |
| Engine maintenance stand |
| Wheel Quantity: |
| 1 |
| Safe Operating Load Rating: |
| 200.00 pounds |
| Material And Location: |
| Steel body and rubber, hard tire |
| Surface Treatment And Location: |
| Zinc plated body |
| Wheel Type: |
| Solid |
| Wheel Diameter: |
| 4.00 inches |
| Effective Height: |
| 5.50 inches |
| Plate Style: |
| Square |
| Wheel Bearing Type: |
| Plain, self-lubricated |
| Tread Width: |
| 2.00 inches |
| Caster Plate Length: |
| 4.50 inches |
| Caster Plate Width: |
| 4.00 inches |
| Caster Plate Mounting Slot Length: |
| 0.75 inches |
| Caster Plate Mounting Hole Diameter: |
| 0.438 inches |
| Product Name: |
| Caster |
| Style Designator: |
| Rigid |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5340-01-605-2604

Swivel Caster - Page 2 of 2



Demilitarization:

No

Fiig:

A25600