NSN 5340-01-605-3561

Spacing Threaded Standoff - Page 1 of 2



/iew Online at https://aerobasegroup.com/psp/5340-01-605-3561

View Online at https://aerobasegroup.com/nsn/5340-01-605-3561
Thread Class:
3b left internal (includes through thread)
Thread Direction:
Right-hand left internal (includes through thread)
Flange Diameter:
1.250 inches
Flange Thickness:
0.100 inches
Length:
0.462 inches
Cross-sectional Length:
2.000 inches
Cross-sectional Width:
0.900 inches
End Application:
Rq-4a
Cross-sectional Shape:
Rectangular
Thready Qty Per Inch (tpi):
32 left internal (includes through thread)
Thread Size:
0.1900 inches left internal (includes through thread)
Product Name:
Standoff, locking thread, adhesive bonded
Material:
Steel comp 302 and steel comp 303 and steel comp 304
Material Specification:
Ams5513 assn standard single material response and ams5516 assn standard single material response and ams5636 assn standard single
material response and ams5637 assn standard single material response and ams5638 assn standard single material response and
ams5639 assn standard single material response and ams5640 assn standard single material response and ams5641 assn standard single
material response and ams5647 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal standard single treatment response
Style Designator:
Flanged left internal thread
Thread Series Designator:
Unf left internal (includes through thread)
Shelf Life:
N/a
Unit Of Measure:

Nic

Demilitarization:

NSN 5340-01-605-3561

Spacing Threaded Standoff - Page 2 of 2



Fiig:

A08900