

View Online at <https://aerobasegroup.com/nsn/5340-01-605-3561>

**Thread Class:**

3b left internal (includes through thread)

**Thread Direction:**

Right-hand left internal (includes through thread)

**Flange Diameter:**

1.250 inches

**Flange Thickness:**

0.100 inches

**Length:**

0.462 inches

**Cross-sectional Length:**

2.000 inches

**Cross-sectional Width:**

0.900 inches

**End Application:**

Rq-4a

**Cross-sectional Shape:**

Rectangular

**Thready Qty Per Inch (tpi):**

32 left internal (includes through thread)

**Thread Size:**

0.1900 inches left internal (includes through thread)

**Product Name:**

Standoff, locking thread, adhesive bonded

**Material:**

Steel comp 302 and steel comp 303 and steel comp 304

**Material Specification:**

Ams5513 assn standard single material response and ams5516 assn standard single material response and ams5636 assn standard single material response and ams5637 assn standard single material response and ams5638 assn standard single material response and ams5639 assn standard single material response and ams5640 assn standard single material response and ams5641 assn standard single material response and ams5647 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal standard single treatment response

**Style Designator:**

Flanged left internal thread

**Thread Series Designator:**

Unf left internal (includes through thread)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A08900