Spacing Threaded Standoff - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-01-608-4768

| In right projection Length:<br>Stallers steel<br>Stallers steel<br>Stallers steel<br>Stallers steel<br>Stallers steel<br>Starler Treatment:<br>Prate Treatment:<br>Passivate<br>Starler Treatment Specification:<br>Ams-qq+35, astm a967 type ii assn standard single treatment response<br>Style Designator:<br>Left internal and right external thread<br>Thread Starle:<br>Starler Treatment:<br>Passivate<br>Starler Treatment Specification:<br>Ams-qq+35, astm a967 type ii assn standard single treatment response<br>Style Designator:<br>Left internal and right external thread<br>Thread Starler Starle | Thread (   | Class:   |
|--|------------|--|
| Right-hand right external   Thread Length:   0.500 inches right external   Length:   1.188 inches   End Application:   5410-01-592-9463   Cross-sectional Shape:   Hexagon   Width Across Flats:   0.500 inches   Thread Qty Per Inch (tpi):   32 right external   Thread Size:   0.190 inches right external   Product Name:   Spacer threaded   Right Projection Diameter:   0.500 inches   Right Projection Length:   0.500 inches   Right Projection Diameter:   0.500 inches   Starles steel   Surface Treatment Specification:   Ams-qu-35, astm a967 type ii assn standard single treatment response   Style Designator:   Left internal and right external thread   Thread Series Designator:   Uri right external   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:  | 2a right e | external   |
| Thread Length:<br>0.500 inches right external<br>Length:<br>1.188 inches<br>End Application:<br>5410-01-592-9463<br>Cross-sectional Shape:<br>Hexagon<br>Width Across Flats:<br>0.500 inches<br>Thready Qty Per Inch (tpl):<br>32 right external<br>Thread Size:<br>0.190 inches right external<br>Product Name:<br>Spacer threaded<br>Right Projection Diameter:<br>0.500 inches<br>Right Projection Length:<br>0.500 inches<br>Surface Treatment:<br>Passivate<br>Stainless steel<br>Sturface Treatment Specification:<br>Ams-qq+35, astm a967 type ii assn standard single treatment response<br>Style Designator:<br>Left internal and right external thread<br>Thread Series Designator:<br>Unf right external<br>Shelf Life:<br>Na<br>Unit Of Measure:<br><br>Demilitarization:  | Thread [   | Direction:   |
| 0.500 inches right external Length: 1.188 inches End Application: 5410-01-592-9463 Cross-sectional Shape: Hexagon Width Across Flats: 0.500 inches Thready Qty Per Inch (tpi): 32 right external Thread Size: 0.190 inches right external Product Name: Spacer threaded Right Projection Diameter: 0.500 inches Material: Stainless steel Surface Treatment: Passivate Surface Treatment Specification: Ams-qq+35, astm a967 type ii assn standard single treatment response Style Designator: Left internal and right external thread Thread Series Designator: Unf right external Shelf Life: Na Unit Of Measure: Demilitarization:  | Right-ha   | nd right external  |
| Length:<br>1.188 inches<br>End Application:<br>5410-01-592-9463<br>Cross-sectional Shape:<br>Hexagon<br>Width Across Flats:<br>0.500 inches<br>Thready Qty Per Inch (tpi):<br>32 right external<br>Thread Size:<br>0.190 inches right external<br>Product Name:<br>Spacer threaded<br>Right Projection Diameter:<br>0.500 inches<br>Right Projection Length:<br>0.500 inches<br>Right Projection Length:<br>0.500 inches<br>Material:<br>Stainless steel<br>Surface Treatment:<br>Passivate<br>Surface Treatment Specification:<br>Arns-qq+35, astm a967 type ii assn standard single treatment response<br>Style Designator:<br>Left internal and right external thread<br>Thread Series Designator:<br>Unf right external<br>Shelf Life:<br>Na<br>Unit Of Measure:<br><br>Demilitarization:  | Thread L   | ength:   |
| A la sinches End Application: 5410-01-592-9463 Cross-sectional Shape: Hexagon Width Across Flats: 0.500 inches Thready Qty Per Inch (tpi): 32 right external Thread Size: 0.190 inches right external Product Name: Spacer threaded Right Projection Diameter: 0.500 inches Right Projection Length: 0.500 inches Material: Stainless steel Surface Treatment: Passivate Surface Treatment Specification: Ams-qq+35, astm a967 type ii assm standard single treatment response Style Designator: Left internal and right external thread Thread Series Designator: Unf right external Sheft Life: Na Unit of Measure: Demilitarization:  | 0.500 inc  | hes right external   |
| End Application:<br>5410-01-592-9463<br>Cross-sectional Shape:<br>Hexagon<br>Width Across Flats:<br>0.500 inches<br>Thready Qty Per Inch (tpi):<br>32 right external<br>Thread Size:<br>0.190 inches right external<br>Product Name:<br>Spacer threaded<br>Right Projection Diameter:<br>0.500 inches<br>Right Projection Length:<br>0.500 inches<br>Material:<br>Stainless steel<br>Surface Treatment:<br>Passivate<br>Surface Treatment Specification:<br>Arms-qa+35, astm a967 type ii assm standard single treatment response<br>Style Designator:<br>Left internal and right external thread<br>Thread Series Designator:<br>Unf right external<br>Shelf Life:<br>N/a<br>Unit of Measure:<br><br>Demilitarization:  | Length:    |  |
| S410-01-592-9483   Cross-sectional Shape:   Hexagon   Width Across Flats:   0.500 inches   Thready Qty Per Inch (tpi):   32 right external   Thread Size:   0.190 inches right external   Product Name:   Spacer threaded   Right Projection Diameter:   0.500 inches   Right Projection Length:   0.500 inches   Material:   Stailes steel   Surface Treatment Specification:   Ams-q+-35, astm a967 type ii assn standard single treatment response   Style Designator:   Left internal and right external thread   Thread Series Designator:   Uni fight external   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:  | 1.188 inc  | hes  |
| Cross-sectional Shape:<br>Hexagon<br>Width Across Flats:<br>0.500 inches<br>Thready Qty Per Inch (tpi):<br>32 right external<br>Thread Size:<br>0.190 inches right external<br>Product Name:<br>Spacer threaded<br>Right Projection Diameter:<br>0.500 inches<br>Right Projection Length:<br>0.500 inches<br>Right Projection Length:<br>0.500 inches<br>Material:<br>Stainless steel<br>Surface Treatment:<br>Passivate<br>Surface Treatment:<br>Passivate<br>Surface Treatment:<br>Passivate<br>Surface Treatment:<br>Passivate<br>Surface Treatment:<br>Passivate<br>Surface Treatment Specification:<br>Ams-qq-+35, astm a967 type ii assn standard single treatment response<br>Style Designator:<br>Left internal and right external thread<br>Thread Series Designator:<br>Unf right external<br>Shelf Life:<br>Na<br>Unit Of Measure:<br><br>Demilitarization:   | End App    | lication:  |
| Hexagon Width Across Flats: 0.500 inches Thready Qty Per Inch (tpi): 32 right external Thread Size: 0.190 inches right external Product Name: Spacer threaded Right Projection Diameter: 0.500 inches Right Projection Length: 0.500 inches Right Projection Length: 0.500 inches Surface Treatment: Passivate Surface Treatment: Passivate Surface Treatment Specification: Ams-qq-+35, astm a967 type ii assm standard single treatment response Style Designator: Left internal and right external thread Thread Series Designator: Unf right external Shelf Life: N/a Unit Of Measure: Demilitarization:   | 5410-01-   | 592-9463   |
| With Across Flats:<br>0.500 inches<br>Thready Qty Per Inch (tpi):<br>32 right external<br>Thread Size:<br>0.190 inches right external<br>Product Name:<br>Spacer threaded<br>Right Projection Diameter:<br>0.500 inches<br>Right Projection Length:<br>0.500 inches<br>Material:<br>Stainless steel<br>Surface Treatment:<br>Passivate<br>Surface Treatment Specification:<br>Arms-qq-+35, astm a967 type ii assn standard single treatment response<br>Style Designator:<br>Left internal and right external thread<br>Thread Series Designator:<br>Unf right external<br>Shelf Life:<br>N/a<br>Unit of Measure:<br><br>Demilitarization:   | Cross-se   | ectional Shape:  |
| 0.500 inches<br>Thready Qty Per Inch (tpi):<br>32 right external<br>Thread Size:<br>0.190 inches right external<br>Product Name:<br>Spacer threaded<br>Right Projection Diameter:<br>0.500 inches<br>Right Projection Length:<br>0.500 inches<br>Material:<br>Stainless steel<br>Surface Treatment:<br>Passivate<br>Surface Treatment Specification:<br>Ams-qq.+35, astm a967 type ii assn standard single treatment response<br>Style Designator:<br>Left internal and right external thread<br>Thread Series Designator:<br>Unf right external<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br><br>Demilitarization:  | Hexagon    |  |
| Thready Qty Per Inch (tpi):<br>32 right external<br>Thread Size:<br>0.190 inches right external<br>Product Name:<br>Spacer threaded<br>Right Projection Diameter:<br>0.500 inches<br>Right Projection Length:<br>0.500 inches<br>Material:<br>Stainless steel<br>Surface Treatment:<br>Passivate<br>Surface Treatment Specification:<br>Ams-qq-+35, astm a967 type ii assn standard single treatment response<br>Style Designator:<br>Left internal and right external thread<br>Thread Series Designator:<br>Unf right external<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br><br>Demilitarization:  | Width A    | cross Flats:   |
| 32 right external<br>Thread Size:<br>0.190 inches right external<br>Product Name:<br>Spacer threaded<br>Right Projection Diameter:<br>0.500 inches<br>Right Projection Length:<br>0.500 inches<br>Material:<br>Stainless steel<br>Surface Treatment:<br>Passivate<br>Surface Treatment Specification:<br>Ams-qq-+35, astm a967 type ii assn standard single treatment response<br>Style Designator:<br>Left internal and right external thread<br>Thread Series Designator:<br>Unf right external<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br><br>Demilitarization:   | 0.500 inc  | hes  |
| Normal Size:         0.190 inches right external         Product Name:         Spacer threaded         Right Projection Diameter:         0.500 inches         Right Projection Length:         0.500 inches         Material:         Stainless steel         Surface Treatment:         Passivate         Surface Treatment Specification:         Ams-qq:+35, astm a967 type ii assn standard single treatment response         Style Designator:         Left internal and right external thread         Thread Series Designator:         Unf right external         Shelf Life:         N/a         Unit Of Measure:            Demilitarization:  | Thready    | Qty Per Inch (tpi):  |
| 0.190 inches right external Product Name: Spacer threaded Right Projection Diameter: 0.500 inches Right Projection Length: 0.500 inches Material: Stainless steel Surface Treatment: Passivate Surface Treatment Specification: Ams-qq-+35, astm a967 type ii assn standard single treatment response Style Designator: Left internal and right external thread Thread Series Designator: Unf right external Shelf Life: N/a Unit Of Measure: Demilitarization:  | 32 right e | external   |
| Product Name:<br>Spacer threaded<br>Right Projection Diameter:<br>0.500 inches<br>Right Projection Length:<br>0.500 inches<br>Material:<br>Stainless steel<br>Surface Treatment:<br>Passivate<br>Surface Treatment Specification:<br>Ams-qq-+35, astm a967 type ii assn standard single treatment response<br>Style Designator:<br>Left internal and right external thread<br>Thread Series Designator:<br>Unf right external<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br><br>Demilitarization:   | Thread S   | Size:  |
| Spacer threaded Right Projection Diameter: 0.500 inches Right Projection Length: 0.500 inches Material: Stainless steel Surface Treatment: Passivate Surface Treatment Specification: Ams-qq-+35, astm a967 type ii assm standard single treatment response Style Designator: Left internal and right external thread Thread Series Designator: Unf right external Shelf Life: N/a Unit Of Measure: Demilitarization:  | 0.190 inc  | hes right external   |
| Right Projection Diameter:   0.500 inches   Right Projection Length:   0.500 inches   Material:   Stainless steel   Surface Treatment:   Passivate   Surface Treatment Specification:   Ams-qq-+35, astm a967 type ii assn standard single treatment response   Style Designator:   Left internal and right external thread   Thread Series Designator:   Unf right external   Shelf Life:   N/a   Unit Of Measure:  | Product    | Name:  |
| 0.500 inches Right Projection Length: 0.500 inches Material: Stainless steel Surface Treatment: Passivate Surface Treatment Specification: Ams-qq-+35, astm a967 type ii assn standard single treatment response Style Designator: Left internal and right external thread Thread Series Designator: Unf right external Shelf Life: N/a Unit Of Measure: Demilitarization:   | Spacer tl  | nreaded  |
| Right Projection Length:   0.500 inches   Material:   Stainless steel   Surface Treatment:   Passivate   Surface Treatment Specification:   Ams-qq-+35, astm a967 type ii assn standard single treatment response   Style Designator:   Left internal and right external thread   Thread Series Designator:   Unf right external   Shelf Life:   N/a   Unit Of Measure:  | Right Pr   | ojection Diameter:   |
| 0.500 inches<br>Material:<br>Stainless steel<br>Surface Treatment:<br>Passivate<br>Surface Treatment Specification:<br>Ams-qq-+35, astm a967 type ii assn standard single treatment response<br>Style Designator:<br>Left internal and right external thread<br>Thread Series Designator:<br>Unf right external<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br>  | 0.500 inc  | hes  |
| Material:<br>Stainless steel<br>Surface Treatment:<br>Passivate<br>Surface Treatment Specification:<br>Ams-qq-+35, astm a967 type ii assn standard single treatment response<br>Style Designator:<br>Left internal and right external thread<br>Thread Series Designator:<br>Unf right external<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br>  | Right Pr   | ojection Length:   |
| Stainless steel Surface Treatment: Passivate Surface Treatment Specification: Ams-qq-+35, astm a967 type ii assn standard single treatment response Style Designator: Left internal and right external thread Thread Series Designator: Unf right external Shelf Life: N/a Unit Of Measure: Demilitarization:  | 0.500 inc  | hes  |
| Surface Treatment:<br>Passivate<br>Surface Treatment Specification:<br>Ams-qq-+35, astm a967 type ii assn standard single treatment response<br>Style Designator:<br>Left internal and right external thread<br>Thread Series Designator:<br>Unf right external<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br>  | Material   |  |
| Passivate Surface Treatment Specification: Ams-qq-+35, astm a967 type ii assn standard single treatment response Style Designator: Left internal and right external thread Thread Series Designator: Unf right external Shelf Life: N/a Unit Of Measure: Demilitarization:   | Stainless  | steel  |
| Surface Treatment Specification:<br>Ams-qq-+35, astm a967 type ii assn standard single treatment response<br>Style Designator:<br>Left internal and right external thread<br>Thread Series Designator:<br>Unf right external<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br><br>Demilitarization:  | Surface    | Treatment:   |
| Ams-qq-+35, astm a967 type ii assn standard single treatment response Style Designator: Left internal and right external thread Thread Series Designator: Unf right external Shelf Life: N/a Unit Of Measure: Demilitarization:  | Passivate  | 9  |
| Style Designator:   Left internal and right external thread   Thread Series Designator:   Unf right external   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:  | Surface    | Treatment Specification:                                       |
| Left internal and right external thread<br>Thread Series Designator:<br>Unf right external<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br><br>Demilitarization:  | Ams-qq-    | +35, astm a967 type ii assn standard single treatment response |
| Thread Series Designator:<br>Unf right external<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br><br>Demilitarization:   | Style De   | signator:  |
| Unf right external Shelf Life: N/a Unit Of Measure: Demilitarization:  | Left inter | nal and right external thread                                  |
| Shelf Life:<br>N/a<br>Unit Of Measure:<br><br>Demilitarization:  | Thread S   | Series Designator:   |
| N/a<br>Unit Of Measure:<br><br>Demilitarization:   | Unf right  | external   |
| Unit Of Measure:<br><br>Demilitarization:  | Shelf Lif  | e:   |
| <br>Demilitarization:  | N/a        |  |
| Demilitarization:  | Unit Of I  | leasure:   |
|  |            |  |
| No   | Demilita   | rization:  |
|  | No         |  |