

View Online at <https://aerobasegroup.com/nsn/5340-01-609-9597>

**First Leg Length:**

Between 2.19 inches and 2.31 inches

**Second Leg Length:**

Between 3.94 inches and 4.06 inches

**End Application:**

2330-01-508-7887

**Second Leg Width:**

Between 4.44 inches and 4.56 inches

**Second Leg Corner Radius:**

0.25 inches

**First Leg Hole Diameter:**

Between 0.282 inches and 0.342 inches

**Second Leg Hole Diameter:**

Between 2.751 inches and 2.811 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 2.69 inches and 2.81 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 1.75 inches and 1.87 inches

**First Leg Thickness:**

0.1196 inches

**Second Leg Thickness:**

0.1196 inches

**First Leg Width:**

Between 1.94 inches and 2.06 inches

**First Leg Corner Radius:**

0.25 inches

**First Leg Distance Between Hole Centers Along Width:**

Between 0.78 inches and 0.84 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.60 inches and 0.66 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.31 inches and 0.43 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

One hole

**Hole Quantity:**

3

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

0.25 radians

**Product Name:**

Bracket, abs warning light, lhst

**Special Features:**

Material is hot rolled. Hot dip galvanize finish per astm a123/a123m-02, grade 50. Final protective finish per 12420325 method 5 or 4

**Material:**

Steel

**Material Specification:**

Astm a36/a36m assn standard single material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0