

View Online at <https://aerobasegroup.com/nsn/5340-01-609-9597>

First Leg Length:

Between 2.19 inches and 2.31 inches

Second Leg Length:

Between 3.94 inches and 4.06 inches

End Application:

2330-01-508-7887

Second Leg Width:

Between 4.44 inches and 4.56 inches

Second Leg Corner Radius:

0.25 inches

First Leg Hole Diameter:

Between 0.282 inches and 0.342 inches

Second Leg Hole Diameter:

Between 2.751 inches and 2.811 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 2.69 inches and 2.81 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 1.75 inches and 1.87 inches

First Leg Thickness:

0.1196 inches

Second Leg Thickness:

0.1196 inches

First Leg Width:

Between 1.94 inches and 2.06 inches

First Leg Corner Radius:

0.25 inches

First Leg Distance Between Hole Centers Along Width:

Between 0.78 inches and 0.84 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.60 inches and 0.66 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.31 inches and 0.43 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

One hole

Hole Quantity:

3

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

0.25 radians

Product Name:

Bracket, abs warning light, lhst

Special Features:

Material is hot rolled. Hot dip galvanize finish per astm a123/a123m-02, grade 50. Final protective finish per 12420325 method 5 or 4

Material:

Steel

Material Specification:

Astm a36/a36m assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0