

View Online at <https://aerobasegroup.com/nsn/5340-01-611-4673>

Mounting Hole Type:

Plain and countersunk

First Leg Length:

0.50 inches

Second Leg Length:

1.12 inches

End Application:

Part number 12437285-4

Second Leg Width:

3.50 inches

First Leg Hole Diameter:

Between 0.242 inches and 0.246 inches

Second Leg Hole Diameter:

Between 0.219 inches and 0.222 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.24 inches and 0.26 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.250 inches

Second Leg Distance Between First And Second Hole Centers Along Length:

1.500 inches

Second Leg Distance Between Second And Third Hole Centers Along Length:

1.500 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

3.50 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.24 inches and 0.26 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Distance Between First And Second Hole Centers Along Length:

1.500 inches

First Leg Distance Between Second And Third Hole Centers Along Length:

1.500 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Three holes

Hole Quantity:

6

Second Leg Relationship To First Leg:

Identical

First Leg Angle:

0.02 radians

Product Name:

Bracket

Special Features:

Holes on first leg are plain and holes on second leg are countersunk 82deg to 0.400min/0.410max depth; see drawing for additional information

Material:

Aluminum alloy 2024 and aluminum alloy 6061

Material Specification:

Qq-a-225/6, qq-a-225/8, qq-a-200/3 or qq-a-200/8 t4 or t6 federal specification single material response

Surface Treatment Specification:

Mil-std-171 7.2.2 military standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-std-171 spec.