NSN 5340-01-611-5397

Spacing Threaded Standoff - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-611-5397

| View Online at https://aerobasegroup.com/nsn/5340-01-61 |
|---|
| Thread Class: |
| 2b left internal (includes through thread) |
| Thread Direction: |
| Right-hand right external |
| Thread Length: |
| 0.188 inches right external |
| Length: |
| Between 0.370 inches and 0.380 inches |
| End Application: |
| 5340-01-414-2248 |
| Cross-sectional Shape: |
| Hexagon |
| Width Across Flats: |
| Between 0.182 inches and 0.194 inches |
| Thready Qty Per Inch (tpi): |
| 56 left internal (includes through thread) |
| Thread Size: |
| 0.486 inches left internal (includes through thread) |
| Product Name: |
| Post, electrical-mechanical equipment, stud type |
| Right Projection Diameter: |
| 0.112 inches |
| Right Projection Length: |
| Between 0.184 inches and 0.192 inches |
| Material: |
| Steel comp 303 or steel comp 303se |
| Material Specification: |
| Astm a582 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-a-35 federal specification single treatment response |
| Style Designator: |
| Left internal and right external thread |
| Thread Series Designator: |
| Unc right external |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5340-01-611-5397

Spacing Threaded Standoff - Page 2 of 2



Fiig:

A08900