

View Online at <https://aerobasegroup.com/nsn/5340-01-611-9696>

Material Thickness:

0.050 inches

First Leg Length:

0.75 inches

Second Leg Length:

0.8755 inches

End Application:

C130 amp cmb

Second Leg Width:

0.800 inches

Second Leg Corner Radius:

0.125 inches

First Leg Hole Diameter:

0.250 inches

Second Leg Hole Diameter:

0.098 inches

Second Leg Distance Between Hole Centers Along Width:

0.375 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

0.338 inches

Second Leg Distance Between Second And Third Hole Centers Along Width:

0.188 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.188 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.250 inches

Second Leg Distance Between First And Second Hole Centers Along Length:

0.375 inches

Second Leg Distance Between Second And Third Hole Centers Along Length:

0.188 inches

First Leg Thickness:

0.050 inches

Second Leg Thickness:

0.050 inches

Center Section Height:

1.0 inches

Center Section Width:

0.800 inches

Center Section Thickness:

0.050 inches

First Leg Width:

0.800 inches

First Leg Corner Radius:

0.125 inches

First Leg Distance From Edge To Hole Center Along Width:

0.400 inches

First Leg Distance From Edge To Hole Center Along Length:

0.400 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

Second Leg Angle:

90.0 degrees

Material:

Aluminum alloy 2024

Surface Treatment Specification:

Chem film gold per ump-pr-che-001 mfr ref single treatment response

Style Designator:

Offset double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0