

View Online at <https://aerobasegroup.com/nsn/5340-01-611-9696>

**Material Thickness:**

0.050 inches

**First Leg Length:**

0.75 inches

**Second Leg Length:**

0.8755 inches

**End Application:**

C130 amp cmb

**Second Leg Width:**

0.800 inches

**Second Leg Corner Radius:**

0.125 inches

**First Leg Hole Diameter:**

0.250 inches

**Second Leg Hole Diameter:**

0.098 inches

**Second Leg Distance Between Hole Centers Along Width:**

0.375 inches

**Second Leg Distance Between First And Second Hole Centers Along Width:**

0.338 inches

**Second Leg Distance Between Second And Third Hole Centers Along Width:**

0.188 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.188 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.250 inches

**Second Leg Distance Between First And Second Hole Centers Along Length:**

0.375 inches

**Second Leg Distance Between Second And Third Hole Centers Along Length:**

0.188 inches

**First Leg Thickness:**

0.050 inches

**Second Leg Thickness:**

0.050 inches

**Center Section Height:**

1.0 inches

**Center Section Width:**

0.800 inches

**Center Section Thickness:**

0.050 inches

**First Leg Width:**

0.800 inches

**First Leg Corner Radius:**

0.125 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.400 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.400 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

Four holes

**Second Leg Relationship To First Leg:**

Not identical

**Second Leg Angle:**

90.0 degrees

**Material:**

Aluminum alloy 2024

**Surface Treatment Specification:**

Chem film gold per ump-pr-che-001 mfr ref single treatment response

**Style Designator:**

Offset double angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0