

View Online at <https://aerobasegroup.com/nsn/5340-01-612-4669>

Cross Sectional Shape:

Flat

Hole Diameter:

Between 0.10 inches and 0.14 inches

Width:

Between 26.53 inches and 26.57 inches

Edge Shape:

Rectangle, multi holes

Length:

Between 18.63 inches and 18.67 inches

Hole Quantity Along Length:

12

Hole Quantity Along Width:

16

Distance Between Holes Along Length:

2.91 inches

Distance Between Holes Along Width:

3.24 inches

Distance Between Hole Centerline And First Hole Along Length:

1.70 inches

Distance Between Hole Centerline And First Hole Along Width:

1.54 inches

Distance From First Hole Centerline To End Along Length:

Between 2.02 inches and 2.06 inches

Distance From First Hole Centerline To End Along Width:

Between 1.90 inches and 1.94 inches

Body Thickness:

0.09 inches

Securing Device Type:

Threaded fastener

Mounting Opening Shape Style:

Unthreaded hole

End Application:

5411-01-581-2654

Special Features:

For aluminum substrates, chemical conversion is required per mil-dtl-5541, class 3, material form 2, method c. Refer to mil-dtl-81706 and qpl-81706 for qualified materials. Finish is powder coating type 4 (tgic), class 3 per mil-prf-24712. The color shall be seafoam green per fed-std-595, 24533.

Material:

Aluminum alloy 5052

Material Specification:

Astm b209, 5052-h32 assn standard single material response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A531c0

Mil-std (military Standard):

Mil-dtl-5541 spec.