

View Online at <https://aerobasegroup.com/nsn/5340-01-612-4669>

**Cross Sectional Shape:**

Flat

**Hole Diameter:**

Between 0.10 inches and 0.14 inches

**Width:**

Between 26.53 inches and 26.57 inches

**Edge Shape:**

Rectangle, multi holes

**Length:**

Between 18.63 inches and 18.67 inches

**Hole Quantity Along Length:**

12

**Hole Quantity Along Width:**

16

**Distance Between Holes Along Length:**

2.91 inches

**Distance Between Holes Along Width:**

3.24 inches

**Distance Between Hole Centerline And First Hole Along Length:**

1.70 inches

**Distance Between Hole Centerline And First Hole Along Width:**

1.54 inches

**Distance From First Hole Centerline To End Along Length:**

Between 2.02 inches and 2.06 inches

**Distance From First Hole Centerline To End Along Width:**

Between 1.90 inches and 1.94 inches

**Body Thickness:**

0.09 inches

**Securing Device Type:**

Threaded fastener

**Mounting Opening Shape Style:**

Unthreaded hole

**End Application:**

5411-01-581-2654

**Special Features:**

For aluminum substrates, chemical conversion is required per mil-dtl-5541, class 3, material form 2, method c. Refer to mil-dtl-81706 and qpl-81706 for qualified materials. Finish is powder coating type 4 (tgic), class 3 per mil-prf-24712. The color shall be seafoam green per fed-std-595, 24533.

**Material:**

Aluminum alloy 5052

**Material Specification:**

Astm b209, 5052-h32 assn standard single material response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A531c0

**Mil-std (military Standard):**

Mil-dtl-5541 spec.