

View Online at <https://aerobasegroup.com/nsn/5340-01-612-7894>

First Leg Length:

Between 2.260 inches and 2.320 inches

Second Leg Length:

Between 5.900 inches and 5.960 inches

Second Leg Width:

Between 6.720 inches and 6.780 inches

Second Leg End Width:

Between 4.720 inches and 4.780 inches

First Leg Slot Length:

Between 0.670 inches and 0.730 inches

First Leg Slot Width:

Between 0.433 inches and 0.443 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 4.765 inches and 4.825 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 4.415 inches and 4.475 inches

Second Leg Slot Length:

Between 0.670 inches and 0.730 inches

Second Leg Slot Width:

Between 0.433 inches and 0.443 inches

First Leg Thickness:

0.188 inches

Second Leg Thickness:

Between 0.660 inches and 0.720 inches

First Leg Distance From Edge To Hole Center Along Width:

1.955 inches

First Leg Distance From Edge To Hole Center Along Length:

1.565 inches

First Leg Style:

Chamfered ends

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

One slot

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

Between 0.330 radians and 0.390 radians

Second Leg Chamfer Angle:

Between 0.970 radians and 1.030 radians

Special Features:

Has 4 welding pads located in diamond formation on leg 2; welding pads are 1.0 inches in diameter and 0.63 inches in height; has 2 rubber pads mounted on top and bottom positioned welding pads of diamond formation; rubber pads are 0.75 inches in diameter and 0.1875 inches in height

Material:

Steel and rubber neoprene

Material Specification:

Astm a 514 assn standard single material response and astm a 36 assn standard single material response and astm d 2000 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0