

View Online at <https://aerobasegroup.com/nsn/5340-01-612-7894>

**First Leg Length:**

Between 2.260 inches and 2.320 inches

**Second Leg Length:**

Between 5.900 inches and 5.960 inches

**Second Leg Width:**

Between 6.720 inches and 6.780 inches

**Second Leg End Width:**

Between 4.720 inches and 4.780 inches

**First Leg Slot Length:**

Between 0.670 inches and 0.730 inches

**First Leg Slot Width:**

Between 0.433 inches and 0.443 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 4.765 inches and 4.825 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 4.415 inches and 4.475 inches

**Second Leg Slot Length:**

Between 0.670 inches and 0.730 inches

**Second Leg Slot Width:**

Between 0.433 inches and 0.443 inches

**First Leg Thickness:**

0.188 inches

**Second Leg Thickness:**

Between 0.660 inches and 0.720 inches

**First Leg Distance From Edge To Hole Center Along Width:**

1.955 inches

**First Leg Distance From Edge To Hole Center Along Length:**

1.565 inches

**First Leg Style:**

Chamfered ends

**Second Leg Style:**

Chamfered ends

**Second Leg Hole Arrangement Style:**

One slot

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

Between 0.330 radians and 0.390 radians

**Second Leg Chamfer Angle:**

Between 0.970 radians and 1.030 radians

**Special Features:**

Has 4 welding pads located in diamond formation on leg 2; welding pads are 1.0 inches in diameter and 0.63 inches in height; has 2 rubber pads mounted on top and bottom positioned welding pads of diamond formation; rubber pads are 0.75 inches in diameter and 0.1875 inches in height

**Material:**

Steel and rubber neoprene

**Material Specification:**

Astm a 514 assn standard single material response and astm a 36 assn standard single material response and astm d 2000 assn standard single material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0