

View Online at <https://aerobasegroup.com/nsn/5340-01-612-9327>

Mounting Hole Type:

Threaded and plain

First Leg Length:

3.340 inches

Second Leg Length:

0.500 inches

End Application:

ELEC-TR-OOP-TICA

Second Leg Width:

1.000 inches

First Leg Hole Diameter:

4.0 millimeters

First Leg Thickness:

0.050 inches

Second Leg Thickness:

0.500 inches

First Leg Width:

1.000 inches

First Leg Corner Radius:

0.250 inches

First Leg Distance Between Hole Centers Along Width:

0.733 inches

First Leg Distance Between Hole Centers Along Length:

0.916 inches

First Leg Distance From Edge To Hole Center Along Width:

0.133 inches

First Leg Distance From Edge To Hole Center Along Length:

0.133 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Four holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

No hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Product Name:

Mounting bracket, outer el pot

Special Features:

Has large mounting hole with 0.753 inch diameter centrally located between 4 mounting holes listed in akau response; has 2 additional threaded mounting holes, having 2-56 unc-2b threading, centrally located 0.346 inches apart at a point 1.250 inches from edge at intersection of leg 2; has 2 additional mounting holes with 0.170 inch diameters centrally located 0.500 inches apart at a point 0.250 inches from edge at intersection of leg 2

Material:

Aluminum alloy 6061

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.