

View Online at <https://aerobasegroup.com/nsn/5340-01-612-9327>

**Mounting Hole Type:**

Threaded and plain

**First Leg Length:**

3.340 inches

**Second Leg Length:**

0.500 inches

**End Application:**

ELEC-TR-OOP-TICA

**Second Leg Width:**

1.000 inches

**First Leg Hole Diameter:**

4.0 millimeters

**First Leg Thickness:**

0.050 inches

**Second Leg Thickness:**

0.500 inches

**First Leg Width:**

1.000 inches

**First Leg Corner Radius:**

0.250 inches

**First Leg Distance Between Hole Centers Along Width:**

0.733 inches

**First Leg Distance Between Hole Centers Along Length:**

0.916 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.133 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.133 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Four holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

No hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Product Name:**

Mounting bracket, outer el pot

**Special Features:**

Has large mounting hole with 0.753 inch diameter centrally located between 4 mounting holes listed in akau response; has 2 additional threaded mounting holes, having 2-56 unc-2b threading, centrally located 0.346 inches apart at a point 1.250 inches from edge at intersection of leg 2; has 2 additional mounting holes with 0.170 inch diameters centrally located 0.500 inches apart at a point 0.250 inches from edge at intersection of leg 2

**Material:**

Aluminum alloy 6061

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-a-8625 spec.