Spacing Threaded Standoff - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-612-9991

#### Thread Class:

3b right internal

#### **Thread Direction:**

Right-hand right internal

#### Thread Length:

0.295 inches right internal

#### Flange Diameter:

1.250 inches

#### Flange Thickness:

0.140 inches

#### Length:

Between 0.480 inches and 0.520 inches

#### **Corner Radius:**

1.050 inches

#### **Cross-sectional Length:**

#### 1.250 inches

Cross-sectional Width:

0.625 inches

#### **End Application:**

DATA-PR-OCE-SSIN

# Cross-sectional Shape:

Elliptical

#### Thready Qty Per Inch (tpi):

32 right internal

#### Thread Size:

0.190 inches right internal

#### **Product Name:**

Post, electri-mechanical equipment-locking thread, bonded

#### **Special Features:**

Standoff having threaded insert of 0.1900-32unf-3b in post with diameterof 0.310 or 0.455 inches; having through (inspection) hole with diameter between 0.062 and 0.070 inches located on body approximately 2 thread pitches from insert

#### Material:

Aluminum alloy or plastic

#### **Material Specification:**

Qq-a-200/3 federal specification single material response or qq-a-225/6 federal specification single material response or qq-a-250/4 federal specification single material response or qq-a-250/8 federal specification single material response or qq-a-250/11 federal specification single material response

#### Surface Treatment:

Anodize

### Surface Treatment Specification:

Mil-a-8625, type 1, class 1 military specification single treatment response

# Style Designator:

Flanged with left internal thread

# Thread Series Designator:

Linf right internal

# NSN 5340-01-612-9991

Spacing Threaded Standoff - Page 2 of 2

AeroBase Group

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A08900

# Mil-std (military Standard):

Mil-a-8625 spec.