

View Online at <https://aerobasegroup.com/nsn/5340-01-616-2613>

Mounting Hole Type:

Plain

First Leg Length:

6.000 inches

Second Leg Length:

14.500 inches

End Application:

Sincgars v (s)

Second Leg Width:

16.130 inches

First Leg Slot Length:

1.000 inches

First Leg Slot Width:

0.200 inches

Second Leg Hole Diameter:

0.406 inches

Second Leg Distance Between Lower Hole Centers Along Width:

13.400 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

13.400 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.360 inches

Second Leg Distance From Edge To Hole Center Along Length:

2.000 inches

Second Leg Distance Between First And Second Hole Centers Along Length:

2.750 inches

Second Leg Distance Between Second And Third Hole Centers Along Length:

8.250 inches

First Leg Thickness:

0.187 inches

Second Leg Thickness:

0.187 inches

First Leg Width:

16.130 inches

First Leg Distance Between Hole Centers Along Width:

12.750 inches

First Leg Distance Between Hole Centers Along Length:

3.000 inches

First Leg Distance From Edge To Hole Center Along Width:

1.390 inches

First Leg Distance From Edge To Hole Center Along Length:

1.250 inches

First Leg Style:

Cut out

First Leg Hole Arrangement Style:

4 slots

Second Leg Style:

Cut out

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

0.190 radians

First Leg Cutout Length:

6.000 inches

First Leg Cutout Width:

8.500 inches

Second Leg Cutout Length:

1.000 inches

Second Leg Cutout Width:

8.500 inches

Special Features:

The braces (tw0) between first and second leg are 11.630 inches (nom) long and one inch (nom) wide

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/b federal specification single material response and astm b 209 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0