NSN 5340-01-616-7207



Flush Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5340-01-616-7207 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.425 inches **Fastener Length:** Between 0.848 inches and 0.878 inches **Head Style:** Oval countersunk undercut **Head Diameter:** Between 0.464 inches and 0.506 inches **Head Height:** 0.111 inches **Grip Diameter:** Between 0.2490 inches and 0.2495 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.428 inches and 0.448 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response and ams4967 assn standard single material response **Surface Treatment:** Aluminum **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1790 professional/industrial association standard

N/a

Shelf Life:

Unit Of Measure:

NSN 5340-01-616-7207 Flush Bolt - Page 2 of 2



em			

No

Fiig:

A10600