

View Online at <https://aerobasegroup.com/nsn/5340-01-618-0173>

**Overall Length:**

3.414 inches

**Overall Width:**

Between 0.59 inches and 0.65 inches

**Material Thickness:**

Between 0.052 inches and 0.072 inches

**Distance Between Mounting Hole Centers:**

Between 2.899 inches and 2.929 inches

**End Application:**

B-2 bomber

**Cushioning Material:**

Plastic, polytetrafluoroethylene

**Cushion:**

Included

**Mounting Pad:**

Not included

**Mounting Hole Size:**

Between 0.194 inches and 0.214 inches

**Distance Between Base And Inside Of Arch:**

2.249 inches

**Inside Diameter/arch Length:**

Between 2.110 inches and 2.140 inches

**Arch Quantity:**

1

**Product Name:**

Clamp, loop, cushioned, saddle

**Special Features:**

The cushion is surface treated with sodium to decrease slippage. The temp ranges for the cushion is -320 - 500 degrees f. And the range for the strap is -320 - 600 degrees f. The strap finish is passivated per ams2700, method 1, class 4.

**Material:**

Steel, ams 5516 or steel, ams 5510 or steel, ams 5513

**Material:**

Steel comp 302 or steel comp 321 or steel comp 304

**Surface Treatment:**

Passivate

**Style Designator:**

Saddle arch

**Surface Treatment:**

Passivated

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T372-a