Block Clamp - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-620-2271

verall Length: 938 inches verall Height: 813 inches 813 inches verall Width: 375 inches outring Hole Diameter: etween 0.190 inches and 0.196 inches outring Hole Quantity: etween 0.190 inches and 0.196 inches outring Hole Quantity: 188 inches 188 inches 188 inches 198
verall Height: 813 inches 813 inches 975 inches 9000000000000000000000000000000000000
813 inches verall Width: 375 inches ounting Hole Diameter: etween 0.190 inches and 0.196 inches ounting Hole Quantity: istance From Center Of Mounting Hole To Edge Along The Width: 188 inches Ind Application: -2a aircraft enter To Center Distance Between First And Third Mounting Holes: 438 inches ounting Facility: Inthreaded hole
verall Width: 375 inches ounting Hole Diameter: atween 0.190 inches and 0.196 inches ounting Hole Quantity: istance From Center Of Mounting Hole To Edge Along The Width: 188 inches Ind Application: -2a aircraft enter To Center Distance Between First And Third Mounting Holes: 438 inches ounting Facility: hthreaded hole
375 inches ounting Hole Diameter: etween 0.190 inches and 0.196 inches ounting Hole Quantity: istance From Center Of Mounting Hole To Edge Along The Width: 188 inches Ind Application: -2a aircraft enter To Center Distance Between First And Third Mounting Holes: 438 inches ounting Facility: inthreaded hole
ounting Hole Diameter: etween 0.190 inches and 0.196 inches ounting Hole Quantity: istance From Center Of Mounting Hole To Edge Along The Width: 188 inches Ind Application: -2a aircraft enter To Center Distance Between First And Third Mounting Holes: 438 inches ounting Facility: hthreaded hole
etween 0.190 inches and 0.196 inches ounting Hole Quantity: istance From Center Of Mounting Hole To Edge Along The Width: 188 inches Ind Application: -2a aircraft enter To Center Distance Between First And Third Mounting Holes: 438 inches ounting Facility: Inthreaded hole
ounting Hole Quantity: istance From Center Of Mounting Hole To Edge Along The Width: 188 inches Ind Application: -2a aircraft enter To Center Distance Between First And Third Mounting Holes: 438 inches ounting Facility: hthreaded hole
Astance From Center Of Mounting Hole To Edge Along The Width: 188 inches Ind Application: -2a aircraft enter To Center Distance Between First And Third Mounting Holes: 438 inches ounting Facility: hthreaded hole
188 inches <b>nd Application:</b> -2a aircraft <b>enter To Center Distance Between First And Third Mounting Holes:</b> 438 inches <b>ounting Facility:</b> hthreaded hole
188 inches <b>nd Application:</b> -2a aircraft <b>enter To Center Distance Between First And Third Mounting Holes:</b> 438 inches <b>ounting Facility:</b> hthreaded hole
nd Application: -2a aircraft enter To Center Distance Between First And Third Mounting Holes: 438 inches ounting Facility: nthreaded hole
-2a aircraft enter To Center Distance Between First And Third Mounting Holes: 438 inches ounting Facility: nthreaded hole
enter To Center Distance Between First And Third Mounting Holes: 438 inches ounting Facility: nthreaded hole
438 inches ounting Facility: nthreaded hole
ounting Facility: hthreaded hole
nthreaded hole
amping Hole Quantity:
amping Hole Diameter:
625 inches second hole
istance From End To First Mounting Hole Center:
250 inches
roduct Name:
ube clamp
pecial Features:
amp block: 3 sections
aterial:
astic phenolic
aterial Specification:
il-p-15035 type fbm military specification all material responses
yle Designator:
ectangular
upplementary Features:
ections dimensions: g220-1505-1 (0.438 x 0.500 x 2.063 in.) + g220-1505-2 (0.750 x 0.500 x 2.063 in.) + g220-1505-3 (0.563 x 0.500 x
063 in.)
helf Life:
/a
nit Of Measure:
emilitarization:

No

## NSN 5340-01-620-2271

Block Clamp - Page 2 of 2

Fiig:

A105a0

Mil-std (military Standard):

Mil-p-15035 spec.

