

View Online at <https://aerobasegroup.com/nsn/5340-01-620-5699>

Mounting Hole Type:

Plain

First Leg Length:

0.880 inches

Second Leg Length:

3.880 inches

End Application:

2350-01-369-6082

Second Leg Width:

3.250 inches

First Leg Hole Diameter:

Between 0.436 inches and 0.453 inches

Second Leg Distance Between Hole Centers Along Width:

2.375 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.4375 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.656 inches

Second Leg Slot Length:

0.500 inches

Second Leg Slot Width:

0.312 inches

First Leg Thickness:

0.065 inches

Second Leg Thickness:

0.065 inches

First Leg Width:

1.090 inches

First Leg End Width:

Between 0.070 inches and 1.030 inches

First Leg Distance From Edge To Hole Center Along Width:

0.540 inches

First Leg Distance From Edge To Hole Center Along Length:

0.440 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Cut out

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

0.090 radians

Second Leg Cutout Length:

0.750 inches

Second Leg Cutout Width:

1.125 inches

First Leg Chamfer Angle:

Between 40.0 degrees and 50.0 degrees

Product Name:

Bracket, electrical connector

Special Features:

Two 0.164 inch mounting holes in second leg

Material:

Steel

Material Specification:

Astma569 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416 assn standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0