NSN 5340-01-620-8068

Spacing Threaded Standoff - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-620-8068

view Offilitie at https://defobasegroup.com/hsh/oo+o-o1-o2o-oooo
Thread Class:
3b left internal (includes through thread)
Thread Direction:
Right-hand left internal (includes through thread)
Thread Length:
0.472 inches left internal (includes through thread)
Flange Diameter:
1.250 inches
Flange Thickness:
0.100 inches
Diameter:
0.310 inches
Length:
Between 0.692 inches and 0.732 inches
End Application:
1520-01-599-2203
Cross-sectional Shape:
Round
Thready Qty Per Inch (tpi):
32 left internal (includes through thread)
Thread Size:
0.1900 inches left internal (includes through thread)
Product Name:
Standoff, locking thread, adhesive bonded
Material:
Aluminum alloy 2024 or aluminum alloy 6061
Material Specification:
Astm b 221, qq-a-225 assn standard single material response or astm b 221, qq-a-250 assn standard single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625 military specification single treatment response
Style Designator:
Flanged left internal thread
Thread Series Designator:
Unf left internal (includes through thread)
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

NSN 5340-01-620-8068

Spacing Threaded Standoff - Page 2 of 2



Fiig:

A08900

Mil-std (military Standard):

Mil-a-8625 spec.