

View Online at <https://aerobasegroup.com/nsn/5340-01-620-8398>

First Leg Length:

Between 3.39 inches and 3.51 inches

Second Leg Length:

Between 10.19 inches and 10.31 inches

Second Leg Width:

Between 3.44 inches and 3.56 inches

First Leg Hole Diameter:

Between 0.300 inches and 0.320 inches

Second Leg Hole Diameter:

Between 0.210 inches and 0.220 inches

Second Leg Distance Between Hole Centers Along Width:

1.104 inches

Second Leg Distance Between Hole Centers Along Length:

1.500 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.206 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.550 inches

First Leg Thickness:

Between 0.345 inches and 0.405 inches

Second Leg Thickness:

Between 0.345 inches and 0.405 inches

First Leg Width:

Between 3.44 inches and 3.56 inches

First Leg Distance Between Upper Hole Centers Along Width:

2.000 inches

First Leg Distance Between Hole Centers Along Length:

1.000 inches

First Leg Distance Between First And Second Hole Centers Along Width:

1.000 inches

First Leg Distance From Edge To Hole Center Along Width:

0.750 inches

First Leg Distance From Edge To Hole Center Along Length:

1.750 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

Four holes

Hole Quantity:

7

Second Leg Relationship To First Leg:

Not identical

Product Name:

Bracket, pda

Material:

Aluminum alloy 5086 or aluminum alloy 5052

Material Specification:

Astm b209 assn standard all material responses

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0