

View Online at <https://aerobasegroup.com/nsn/5340-01-622-9854>

**Mounting Hole Type:**

Plain

**First Leg Length:**

44.44 inches

**Second Leg Length:**

44.44 inches

**End Application:**

5410-01-592-9463

**Second Leg Width:**

1.25 inches

**First Leg Slot Length:**

0.312 inches

**First Leg Slot Width:**

0.38 inches

**Second Leg Distance Between Hole Centers Along Width:**

23.00 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.45 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

10.66 inches

**Second Leg Slot Length:**

6.88 inches

**Second Leg Slot Width:**

0.90 inches

**First Leg Thickness:**

0.125 inches

**Second Leg Thickness:**

0.125 inches

**First Leg Width:**

1.25 inches

**First Leg Distance Between First And Second Hole Centers Along Width:**

12.50 inches

**First Leg Distance Between Second And Third Hole Centers Along Width:**

11.50 inches

**First Leg Distance From Edge To Hole Center Along Width:**

2.195 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.88 inches and 0.92 inches

**First Leg Distance Between Third And Fourth Hole Centers Along Width:**

12.00 inches

**First Leg Style:**

Square

First Leg Hole Arrangement Style:

5 slots

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

2 slots

Hole Quantity:

5

Features Provided:

Notched slide

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

First Leg Distance Between Fourth And Fifth Hole Centers Along Width:

5.62 inches

Product Name:

Angle, retainer, insulation

Special Features:

Color is seafoam green; mark iaw mil-std-130 by rubber stamp or stencil

Material:

Aluminum alloy 6063

Material Specification:

Astm b221 assn standard single material response

Surface Treatment:

Primer and paint

Surface Treatment Specification:

Clean, pretreat, prime and paint iaw 17-3-3208 mfr ref single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-std-130 spec.