

View Online at <https://aerobasegroup.com/nsn/5340-01-622-9854>

Mounting Hole Type:

Plain

First Leg Length:

44.44 inches

Second Leg Length:

44.44 inches

End Application:

5410-01-592-9463

Second Leg Width:

1.25 inches

First Leg Slot Length:

0.312 inches

First Leg Slot Width:

0.38 inches

Second Leg Distance Between Hole Centers Along Width:

23.00 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.45 inches

Second Leg Distance From Edge To Hole Center Along Length:

10.66 inches

Second Leg Slot Length:

6.88 inches

Second Leg Slot Width:

0.90 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

1.25 inches

First Leg Distance Between First And Second Hole Centers Along Width:

12.50 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

11.50 inches

First Leg Distance From Edge To Hole Center Along Width:

2.195 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.88 inches and 0.92 inches

First Leg Distance Between Third And Fourth Hole Centers Along Width:

12.00 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

5 slots

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

2 slots

Hole Quantity:

5

Features Provided:

Notched slide

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

First Leg Distance Between Fourth And Fifth Hole Centers Along Width:

5.62 inches

Product Name:

Angle, retainer, insulation

Special Features:

Color is seafoam green; mark iaw mil-std-130 by rubber stamp or stencil

Material:

Aluminum alloy 6063

Material Specification:

Astm b221 assn standard single material response

Surface Treatment:

Primer and paint

Surface Treatment Specification:

Clean, pretreat, prime and paint iaw 17-3-3208 mfr ref single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-std-130 spec.