NSN 5340-01-623-0217



Angle Bracket - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5340-01-623-0217 **Mounting Hole Type:** Plain First Leg Length: 25.34 inches Second Leg Length: 25.34 inches **End Application:** 5410-01-592-9463 Second Leg Width: 1.25 inches First Leg Hole Diameter: 0.312 inches First Leg Thickness: 0.125 inches Second Leg Thickness: 0.125 inches First Leg Width: 1.25 inches First Leg Distance Between Hole Centers Along Width: Between 0.88 inches and 0.92 inches First Leg Distance Between First And Second Hole Centers Along Width: 6.00 inches First Leg Distance Between Second And Third Hole Centers Along Width: 9.00 inches First Leg Distance From Edge To Hole Center Along Width: Between 2.28 inches and 2.32 inches First Leg Distance From Edge To Hole Center Along Length: 2.295 inches First Leg Style: Square First Leg Hole Arrangement Style: Four holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

No hole

Hole Quantity:

4

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

NSN 5340-01-623-0217

Angle Bracket - Page 2 of 2

Mil-std (military Standard):

Mil-std-130 spec.



| Special Features: |
|--|
| Color is seafoam green; identify iaw mil-std-130 by rubber stamp or stencil |
| Material: |
| Aluminum alloy 6063 |
| Material Specification: |
| Astm b221 assn standard single material response |
| Surface Treatment: |
| Primer and paint |
| Surface Treatment Specification: |
| Clean, pretreat, prime and paint iaw 17-3-3208 mfr ref single treatment response |
| Style Designator: |
| Angle |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A042a0 |