

View Online at <https://aerobasegroup.com/nsn/5340-01-624-7052>

**Mounting Hole Type:**

Plain

**First Leg Length:**

1.70 inches

**Second Leg Length:**

0.98 inches

**Second Leg Width:**

Between 0.490 inches and 0.510 inches

**First Leg Hole Diameter:**

Between 0.200 inches and 0.210 inches

**Second Leg Hole Diameter:**

Between 0.260 inches and 0.270 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.225 inches and 0.235 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.740 inches and 0.760 inches

**First Leg Thickness:**

Between 0.056 inches and 0.068 inches

**Second Leg Thickness:**

Between 0.056 inches and 0.068 inches

**First Leg Width:**

Between 0.490 inches and 0.510 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.195 inches and 0.200 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 1.490 inches and 1.510 inches

**First Leg End Radius:**

Between 0.490 inches and 0.510 inches

**Second Leg End Radius:**

Between 0.490 inches and 0.510 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

Between 85.0 degrees and 95.0 degrees

**Product Name:**

Bracket, angle, 90deg, cres uns s41000, .190x.250 bolt

**Special Features:**

Hardness rating is 30-38 hrc

**Material:**

Steel comp 410

**Material Specification:**

Ams 5504 national std/spec single material response

**Style Designator:**

Angle

**Specification Data:**

81343-sae as9601 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0