

View Online at <https://aerobasegroup.com/nsn/5340-01-624-7052>

Mounting Hole Type:

Plain

First Leg Length:

1.70 inches

Second Leg Length:

0.98 inches

Second Leg Width:

Between 0.490 inches and 0.510 inches

First Leg Hole Diameter:

Between 0.200 inches and 0.210 inches

Second Leg Hole Diameter:

Between 0.260 inches and 0.270 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.225 inches and 0.235 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.740 inches and 0.760 inches

First Leg Thickness:

Between 0.056 inches and 0.068 inches

Second Leg Thickness:

Between 0.056 inches and 0.068 inches

First Leg Width:

Between 0.490 inches and 0.510 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.195 inches and 0.200 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 1.490 inches and 1.510 inches

First Leg End Radius:

Between 0.490 inches and 0.510 inches

Second Leg End Radius:

Between 0.490 inches and 0.510 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

Between 85.0 degrees and 95.0 degrees

Product Name:

Bracket, angle, 90deg, cres uns s41000, .190x.250 bolt

Special Features:

Hardness rating is 30-38 hrc

Material:

Steel comp 410

Material Specification:

Ams 5504 national std/spec single material response

Style Designator:

Angle

Specification Data:

81343-sae as9601 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0