

View Online at <https://aerobasegroup.com/nsn/5340-01-626-5982>

**First Leg Length:**

330.2 millimeters

**Second Leg Length:**

146.1 millimeters

**End Application:**

Model aslav, 715623

**First Leg Slot Length:**

38.1 millimeters

**First Leg Slot Width:**

Between 8.8 millimeters and 9.2 millimeters

**Second Leg Distance Between Hole Centers Along Length:**

138.43 millimeters

**Second Leg Distance From Edge To Hole Center Along Width:**

31.75 millimeters

**Second Leg Distance From Edge To Hole Center Along Length:**

58.97 millimeters

**Second Leg Slot Length:**

38.1 millimeters

**Second Leg Slot Width:**

Between 8.8 millimeters and 9.2 millimeters

**First Leg Thickness:**

6.35 millimeters

**Second Leg Thickness:**

6.35 millimeters

**First Leg Width:**

63.5 millimeters

**First Leg End Width:**

50.5 millimeters

**First Leg Distance From Edge To Hole Center Along Width:**

31.75 millimeters

**First Leg Distance From Edge To Hole Center Along Length:**

50.8 millimeters

**First Leg Style:**

Chamfered ends

**First Leg Hole Arrangement Style:**

One slot

**Second Leg Hole Arrangement Style:**

2 slots

**Second Leg Relationship To First Leg:**

Identical

**First Leg Angle:**

90.0 degrees

**First Leg Chamfer Angle:**

45.0 degrees

**Product Name:**

Brace

**Special Features:**

Item is a three-piece welded assembly

**Material:**

Aluminum alloy 6061

**Material Specification:**

Astm b209 or sae-ams-qq-a-250/11-t651 assn standard single material response

**Surface Treatment:**

Paint

**Surface Treatment Specification:**

715721, para 3.2, white mfr ref single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0