

View Online at <https://aerobasegroup.com/nsn/5340-01-626-5982>

First Leg Length:

330.2 millimeters

Second Leg Length:

146.1 millimeters

End Application:

Model aslav, 715623

First Leg Slot Length:

38.1 millimeters

First Leg Slot Width:

Between 8.8 millimeters and 9.2 millimeters

Second Leg Distance Between Hole Centers Along Length:

138.43 millimeters

Second Leg Distance From Edge To Hole Center Along Width:

31.75 millimeters

Second Leg Distance From Edge To Hole Center Along Length:

58.97 millimeters

Second Leg Slot Length:

38.1 millimeters

Second Leg Slot Width:

Between 8.8 millimeters and 9.2 millimeters

First Leg Thickness:

6.35 millimeters

Second Leg Thickness:

6.35 millimeters

First Leg Width:

63.5 millimeters

First Leg End Width:

50.5 millimeters

First Leg Distance From Edge To Hole Center Along Width:

31.75 millimeters

First Leg Distance From Edge To Hole Center Along Length:

50.8 millimeters

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

One slot

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Identical

First Leg Angle:

90.0 degrees

First Leg Chamfer Angle:

45.0 degrees

Product Name:

Brace

Special Features:

Item is a three-piece welded assembly

Material:

Aluminum alloy 6061

Material Specification:

Astm b209 or sae-ams-qq-a-250/11-t651 assn standard single material response

Surface Treatment:

Paint

Surface Treatment Specification:

715721, para 3.2, white mfr ref single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0